

## EXTRUDABLE FLUOROPOLYMER BLENDS

### Technical Field

5        This invention relates to melt processable fluorothermoplastic compositions comprising a blend of different fluoropolymers, as well as methods of improving extrusion properties in extruded fluorothermoplastics.

### Background

10        Fluoropolymers have found wide utility in a vast array of applications. However, they are often beset by processing difficulties. Specific difficulties include surface roughness such as melt fracture and other problems such as die drooling.

15        Higher processing temperatures can reduce some of these problems, but may involve other problems. One such problem is the molecular weight degradation of the fluoropolymer. This can result in reduced physical properties, can contribute to the die drool, and the corrosive by-products can lead to premature wear of the processing equipment.

20        Another alternative to reduce the surface roughness of extrudates is to reduce the processing rate. This increases the residence time of the fluoropolymer in an extruder, which also contributes to degradation. Reducing production rates is also economically undesirable.

25        Decreasing the molecular weight of the input fluoropolymer can allow for limited improvements in output, but this also decreases the mechanical properties of the polymer. Such a mechanical property detriment may then be partially offset by the addition of costly comonomers, but this modification can add production complications and detract from other physical properties.

30        Another approach toward reducing surface defects in fluoropolymers has been to create a mixture of several fluoropolymers having similar composition yet of significantly different molecular weights in attempt to balance the polymer properties with the processing parameters. In theory, a lower molecular weight portion allows for higher output rate with the blend, while a higher molecular weight portion improves the mechanical properties of the blend. This compromise achieves limited success and increases the complexity required to produce such a material.

Yet another approach involved adding a polyolefin to specific fluoropolymers. However, the temperatures necessary for processing fluoropolymers are usually too high for this approach. In addition, such a material can negatively affect properties of the fluoropolymer, such as color, permeation rate, and chemical resistance.

5 JP 60-23701 describes a blend of a fluorinated elastomer and a copolymer of tetrafluoroethylene and hexafluoropropene (FEP) to achieve heat stress-crack resistance. U.S. Patent No. 5,051,479 describes a melt-processable thermoplastic consisting essentially of a blend of a fluoropolymer and an elastomeric tetrafluoroethylene-perfluoro(alkyl vinyl) ether copolymer.

### 10 Summary

Despite these attempts, there is still a great need to be able to process fluoropolymer materials at higher output rates while maintaining a quality finish on the part and without sacrificing mechanical properties.

15 Accordingly, the present invention provides a melt processable fluorothermoplastic composition comprising a major amount of a first semi-crystalline fluorinated copolymer and a minor amount of a second fluoropolymer effective to reduce melt defects in the composition. Each fluoropolymer is selected from four classes. The first class, (a), includes a semi-crystalline perfluorinated copolymer. The second class, (b), includes a fluoropolymer derived from  
20 interpolymerized units of at least one essentially perfluorinated monomer and at least one non-fluorinated hydrogen-containing monomer. The third class, (c), includes a fluoropolymer derived from interpolymerized units of at least one partially-fluorinated monomer, and optionally at least one essentially perfluorinated monomer. The fourth class, (d), includes an amorphous copolymer of tetrafluoroethylene and hexafluoropropylene. When the first  
25 fluoropolymer is selected from (a), the second fluoropolymer is a semi-crystalline fluoropolymer selected from (b) and/or (c). When the first fluoropolymer is selected from (b), the second fluoropolymer is selected from (a), (c), and/or (d). When the first fluoropolymer is a copolymer selected from (c), the second fluoropolymer is selected from (a), (b), and/or (d).

30 In another aspect, the present invention provides a melt processable fluorothermoplastic composition comprising a major amount of a semi-crystalline fluorinated copolymer and a minor amount of a fluoropolymer effective to reduce melt defects (such as melt fracture or surface roughness) in the composition. The second fluoropolymer (minor amount) is selected from an amorphous fluorinated copolymer derived from interpolymerized units of a perfluoro

(alkoxy vinyl) ether and a comonomer which may be partially or fully fluorinated, and/or an amorphous fluorinated copolymer derived from interpolymerized units of at least 3 mole percent (mol%) of an hydrogen containing comonomer, and a perfluoro (alkoxy vinyl) ether and/or a perfluoro (alkyl vinyl) ether. This group of materials may also be used in conjunction with the other minor component fluoropolymers as defined herein.

In another aspect, the present invention provides a method of improving extrusion properties in an extrudate. This method comprises blending a major amount of a first semi-crystalline fluorinated copolymer and a minor amount of a second fluoropolymer effective to improve extrusion properties in the composition, and melt processing the blend to form the extrudate. In this method, each fluoropolymer is selected from one of four classes: (i) a semi-crystalline perfluorinated copolymer; (ii) a fluoropolymer derived from interpolymerized units of at least one essentially perfluorinated monomer and at least one non-fluorinated hydrogen-containing monomer; (iii) a fluoropolymer derived from interpolymerized units of at least one partially-fluorinated monomer, and optionally at least one essentially perfluorinated monomer; and/or (iv) an amorphous fluorinated copolymer derived from interpolymerized units of a perfluoro (alkoxy vinyl) ether and a comonomer which may be partially or fully fluorinated, and/or an amorphous fluorinated copolymer derived from interpolymerized units of at least 3 mole percent (mol%) of an hydrogen containing comonomer, and a perfluoro (alkoxy vinyl) ether and/or a perfluoro (alkyl vinyl) ether. Also in this method, when the first fluoropolymer is selected from (i), the second fluoropolymer is a fluoropolymer selected from at least one material of class (ii), a semi-crystalline material of class (iii), and/or a material from class (iv); when the first fluoropolymer is selected from (ii), the second fluoropolymer is selected from (i), (iii), and/or (iv); and when the first fluoropolymer is a copolymer selected from (iii), the second fluoropolymer is selected from (i), (ii), and/or (iv).

When a fluoropolymer is melt-processed, issues of surface defects, output rates, and mechanical properties must be addressed. Surprisingly, when these same fluoropolymers are used in blends of the present invention, remarkably improved processing flexibility results. The extrudable compositions of the invention are not as prone to the thermal instability issues of known blends. In addition, the end-use properties of articles made from the major component fluoropolymer, such as permeation, extraction, and chemical resistance, can be preserved in the fluoropolymer blends of the present invention.

### Detailed Description

In one aspect of the present invention, a fluoropolymer blend is comprised of combinations of fluoropolymers selected from four distinct classes. Materials are selected from at least two different classes to form the fluoropolymer blend of the invention.

5 The fluoropolymers and fluoropolymer blends of the invention are melt processable. As used herein, "melt processable" means that the material can be repeatedly processed with the assistance of heat. That is, the fluoropolymers and fluoropolymer blends can be extruded without thermosetting or cross-linking.

10 The fluoropolymers of the invention preferably have a melt flow index (MFI) of about 1g per 10 min or greater, under a load of 5 kg at the temperature at which they are to be processed. In general, the fluoropolymers will have a melt viscosity of less than about  $10^6$  Poise at the desired processing temperature. In addition, the molecular weight of the fluoropolymer is sufficiently high so as not to be considered oligomeric, *i.e.*, a number average molecular weight above about 10,000 g/mol.

15 The fluoropolymers in the blend of the invention are selected from four classes. The first class comprises monomers that are essentially perfluorinated. As used herein, "essentially perfluorinated" means that less than about 5 weight percent (wt%), more preferably less than about 1 wt% or even 0 wt%, of the monomers have hydrogen substituents. The other two classes of fluoropolymer in the blend of the invention are partially fluorinated. These  
20 fluoropolymer contain interpolymerized units of hydrogen containing monomers. The constituent fluoropolymers will now be described more particularly.




The first class of fluoropolymers contains interpolymerized units of tetrafluoroethylene (TFE) and at least one other essentially perfluorinated monomer of the general formula (I):  $\text{CF}_2=\text{CFR}$ , wherein R is  $\text{R}_f$ ,  $\text{R}_f\text{X}$ ,  $\text{R}_f'\text{X}$  or  $\text{Cl}$ ; wherein X is F, Cl, Br, or H,  $\text{R}_f$  is a perfluorinated  
25 alkane, and  $\text{R}_f'$  is:  $\text{O}(\text{R}_f^2\text{O})_a(\text{R}_f^3\text{O})_b\text{R}_f^4$  where  $\text{R}_f^2$  and  $\text{R}_f^3$  are the same or are different linear or branched  $\text{C}_1$ - $\text{C}_6$  perfluoroalkylene groups; a and b are, independently, 0 or an integer from 1 to 10; and  $\text{R}_f^4$  is a  $\text{C}_1$ - $\text{C}_6$  perfluoroalkyl group. Examples of the monomers of this formula include hexafluoropropylene (HFP), chlorotrifluoroethylene (CTFE), perfluoroalkyl vinyl ethers (PAVE), and the perfluoroalkoxy vinyl ethers (PAOVE). Examples of the perfluoroalkyl vinyl  
30 ethers include perfluoromethyl vinyl ether (PMVE), perfluoroethyl vinyl ether (PEVE), perfluoropropyl vinyl ether (PPVE), and the like, some of which are shown below.



PMVE



PEVE



5



10

Combinations of perfluoroalkyl vinyl ethers and perfluoroalkoxy vinyl ethers may also be used.

The amount of essentially perfluorinated comonomer present with the TFE in the fully fluorinated polymer is limited to the amounts that allow it to be melt processable and remain a semi-crystalline material. Typically this will range between about 2% and 30% by weight depending on the comonomer chosen and the desired properties of the fluoropolymer. In addition, these materials may be treated with fluorine to further improve their thermal stability by known methods.

15

The second and third classes of fluoropolymers useful in preparation of the invention are referred to as partially fluorinated fluoropolymers, for they contain some constituent hydrogen atoms. Specifically, these fluoropolymers contain interpolymerized units derived from at least one monomer that contains hydrogen. These two classes of partially fluorinated fluoropolymers are distinguished from one another by the type of constituent hydrogen containing interpolymerized units. The monomers used to make the fluoropolymer in the first of these classes contain both non-fluorinated hydrogen-containing monomers and essentially perfluorinated monomers. The monomers used to make the fluoropolymer in the second of these classes include both hydrogen and fluorine.

20

25

The second class of fluoropolymers useful in forming the blend of the present invention comprises interpolymerized units of non-fluorine containing monomers. Such non-fluorine containing monomers useful for copolymerizing with a fluorine containing monomer include ethylene, propylene, and higher alkenes and dienes. These non-fluorine-containing monomers are typically present at a level of at least 5% and are copolymerized with TFE, HFP, and/or combinations of other monomers from Formula I. These materials may be either semi-crystalline or amorphous. In addition they may also contain minor amounts of partially fluorinated monomers, such as vinylidene fluoride (VF2). Typically such monomers are present at a level of less than about 15% by weight, preferably less than about 10% or even about 5%.

30

35

In many instances, these polymers are essentially free of partially fluorinated hydrogen containing monomers, and contain less than 1 wt% or even 0 wt% of these monomers. In particular these monomers may be free of those partially fluorinated hydrogen containing monomers which may detract from the base resistance of the polymer. In other instances, certain specific partially fluorinated monomers, such as perfluorobutyl-ethylene (PFBE), which do not significantly detract from the chemical resistance of the fluoropolymer readily may be used.

The third class of fluoropolymers useful in forming the blend of the present invention is also partially-fluorinated, hydrogen-containing fluoropolymers. These fluoropolymers contain at least 5% by weight of at least one partially fluorinated monomer that contains both hydrogen and fluorine atoms. Suitable monomers include primarily vinylidene fluoride, but also may include vinyl fluoride, and/or tri-fluoroethylene. This third class of copolymers is comprised of either homopolymers of these partially fluorinated monomers or copolymers of these monomers with TFE, HFP, and/or monomers of Formula I. They may also contain below about 5 wt% of other non-fluorinated monomers. This third class of fluoropolymers sometimes has been characterized in the art as having decreased chemical resistance to bases in comparison to the other described groups and may be more prone to dissolution or swelling by hydrocarbon solvents.

The fourth class of fluoropolymers useful in forming the blend of the present invention comprises amorphous copolymers of TFE and HFP.

The melt processable fluoropolymer blend of the invention is formed by blending two or more fluoropolymers selected from at least two of the four above-described groups of fluoropolymers. The first blend component is present in a major amount, *i.e.*, at least about 90 weight percent (wt%), more preferably at least about 95 wt% and often 98 wt% or greater, based on the total blend. This first blend component is chosen for its inherent mechanical or physical properties for a desired application and it imparts these properties to the extrudate. This first blend component is semicrystalline, *i.e.*, it has a discernible melting peak. The major component often is comprised of only one polymer, but it may also comprise two or more fluoropolymer materials that are preferably selected from the same group of fluoropolymers. If two or more fluoropolymers comprise the major component, they should have sufficient compatibility such that they do not significantly phase-separate during extrusion.

Intermediate blends may be produced to contain as low as 90%, 80%, or even 50% of the major component with the minor component making up the difference. These blends may also provide utility in the process of the invention.

The second blend component, which constitutes the minor portion of the fluoropolymer blend, is chosen from one or both of the remaining classes of fluoropolymers that were not selected as the first blend component. This minor blend component may also comprise two or more fluoropolymers selected from one, or both, of the remaining classes. The second blend component normally has a minimal effect, or no apparent effect on the mechanical properties of the extrudate or the finished article in the intended application. It aids the extrusion properties and improves the final surface characteristics of the extrudate. This second blend component is preferably melt-processable at the desired processing conditions of the first blend component.

Typically the minor component is present at a level of less than 5% by weight of the fluoropolymer blend, preferably less than 2%. In many instances, the level of this second component can be much less than 5%, such as 1% or lower, and still provide the significant benefits of the invention. In some aspects, levels of 0.5% or even 0.05% can provide benefits over the major blend component alone.

One helpful criterion for the selection of the minor component is that it should be largely immiscible with the first component. By selecting the minor component from one of the remaining groups of fluoropolymers, other than that chosen from for the major component, this immiscibility may be achieved. A simple test for determining immiscibility involves preparing a blend of the two materials at a temperature above the melting point, or above the melt processing temperature, of either material. At sufficiently high levels of the minor component, the blend component visually will appear more opaque, milky, or cloudy in comparison to either of the individual components. Amounts of the minor component necessary to achieve this affect typically vary from below about 1% up to about 5% by weight based on the total weight of the major and minor components. At lower levels of the minor component, or if the two dissimilar fluoropolymers of the blend have a similar refractive index, this effect may be unnoticed. However, the minor component will remain immiscible and may be detected by known optical microscopy methods.

The immiscibility between the major and minor components of the blend is attributed to the difference in interpolymerized units in the individual polymeric components of the polymer blend. For example, one component may lack a specific monomer that is appreciably present in the other component. These differentiating monomers may be either randomly dispersed

throughout the component polymer, or alternatively they may be more concentrated in certain portions of the polymer such as in a block co-polymer or a core-shell type polymer. Typically this monomeric difference will be in the presence or lack of one of the two types of hydrogen containing monomers.

5 In addition, the fluoropolymer utilized in either component may contain other monomers that augment the immiscibility between the two components. Examples of this include longer chain monomers, which impart side chains when polymerized, or those that impart chemical functionality or may serve to make the polymer chain more polarizable. Examples include, those of Formula I, wherein  $R_f$  contains at least one carbon atom and preferably at least one  
10 oxygen atom. Other possibilities include both fluorinated and/or hydrogenated monomers that contain cyclic or aromatic structures, those substituted with other hetero-atoms, and monomers with chemically-functional groups. It is possible for both components of the fluoropolymer blend to contain some of the same types of monomers, provided that they do not have the adverse effect of making the two polymers compatible or miscible. The more highly modified  
15 material typically should be the minor component of the blend.

In addition to its immiscibility, the minor component will typically have a viscosity that is similar to that of the major component at the intended processing conditions of the blend. The minor component may be comprised of two or more fluoropolymers of significantly different molecular weight and/or composition, and may or may not be miscible with one another. The  
20 combination of the minor components remains immiscible with the major component of the blend. In addition, the minor component will be of appreciable molecular weight such that it does not easily migrate or is not easily extracted from a finished article of the blend. Minor components that are semi-crystalline or are insoluble in common hydrocarbon solvents can also serve to minimize the extractability.

25 The monomeric composition of the minor component may also be chosen to minimize its influence on the physical properties of the major component. For instance if the fluoropolymer blend is used for electrical insulation, the use of monomers which increase the dielectric constant or dissipation factor should be minimized.

The fluoropolymers used in the formation of the blend will contain at least 30% fluorine  
30 by weight and preferably will contain 40% or more. The percent fluorine will also depend on whether the particular fluoropolymer is used as the major or minor component and the intended end use application for the blend. That is, many major component fluoropolymers should contain at least about 60% fluorine and some will contain 70% or more. In one aspect where the



end-use application of the fluoropolymer is wire coating for high speed data transfer, the major component could be an essentially perfluorinated material such as FEP, which can contain up to 76% fluorine by weight. Another example for the major component would be a copolymer of TFE, VF2 and HFP, which contains about 70% fluorine or more, for use as for a flexible fuel  
5 hose barrier. In either case, the minor component used to form the blend could be, for example, a hydrogen-containing fluoropolymer comprising interpolymerized units of ethylene or propylene that contains about 65% to 60% or less of fluorine, or alternatively the minor phase may be an essentially perfluorinated amorphous copolymer of TFE and MV-31.

The major and minor blend components can be combined through any known means.

10 The minor component preferably is well dispersed within the major component of the fluoropolymer blend. The before-mentioned criteria for the selection of the minor component will aid in this dispersion, as will the incorporation and mixing technique chosen to prepare the blend. To effect the desired dispersion within the blend, the two components may be fed in a form such as pellet, powder, flake, or liquid dispersion, to a suitable blending or pre-blending  
15 device. Typical devices for blending the materials in the molten state include single and twin screw extruders and batch mixers. In addition, more than one of these mixing techniques may be used to form the blend in which the minor component is uniformly dispersed and randomly distributed. For instance, a higher amount of the minor component, at levels up to about 20%, may first be blended into the major component using a twin screw extruder. This blend may  
20 then be diluted with more of the major component using another mixing technique to form the final desired composition of the fluoropolymer. This final blending step may also be the same step that is used to form a finished extruded article. When the minor component is well dispersed, the fluoropolymer blend will enhance the performance benefits of the invention. Proper dispersion can also allow for lower use levels of the minor component.

25 When the major component of the blend is comprised of a perfluorinated polymer, the selected fluoropolymer will be copolymers of TFE and at least 2 wt% of one or more comonomers of Formula I. Preferred comonomers include HFP at levels up to about 20 wt% and/or PAVE (perfluoroalkylvinylethers) at levels of up to about 10 wt%. Copolymers of TFE and HFP are commonly referred to as FEP. Copolymers of TFE and PAVE, such as PPVE-1,  
30 are referred to as PFA. Commercially available polymers useful in the is aspect of the invention include FEP 6322, PFA 6502N, PFA FLEX X 6515 UHP from Dyneon LLC (Oakdale, MN); FEP 5100, PFA 950 HP and FEP CJ95 from DuPont (Wilmington, DE), FEP NP101 and PFA 238SH from Daikin (Japan) and MFA 620 from Ausimont (Italy).

The minor component that is blended with the major component perfluorinated polymer will also be semi-crystalline. It is selected from either group of partially fluorinated fluoropolymers. Alternatively, it may be a polymer comprising any combination of the two different types of hydrogen containing monomers with other fluorinated polymers. Examples  
5 include ethylene-tetrafluoroethylene (ETFE), hexafluoropropylene-ethylene-tetrafluoroethylene (HTE), tetrafluoroethylene-propylene (TFE/P), poly (vinylidene fluoride) (PVdF), and tetrafluoroethylene-hexafluoropropylene-vinylidene fluoride (THV).

When the major component is chosen from the group of fluoropolymers that contain  
10 interpolymers lacking fluorine along with fluorinated monomers, the preferred materials are copolymers which contain both ethylene and TFE. Preferably the ethylene content is at least about 10 wt%. Additionally, these polymers may contain HFP, perfluoroalkylvinylethers, and other long chain monomers such as PFBE. Commercially available materials of these preferred polymers include ETFE 6235, ETFE 6235J, HTE X 1510 and HTE X 1705 from Dyneon and EFEP from Daikin.

15 The minor component for this blend can be selected from either the group of fully fluorinated copolymers or from the group of partially fluorinated polymers that are comprised of monomers which contain both fluorine and hydrogen. Examples of this latter group include homopolymers and copolymers of VF2 with monomers of Formula I. A group of preferred materials for the minor component are those that contain substantially lower levels of hydrogen  
20 containing monomers than does the major blend component. Examples of this group include copolymers of TFE with HFP and/or PPVE.

When the major blend component is selected from the group comprised of monomers that contain both hydrogen and fluorine, the fluoropolymer will be a copolymer of VF2 and at least one other copolymerizable comonomer. The preferred materials will contain at least 5 wt%  
25 and preferably 10 wt% and higher of essentially perfluorinated monomers. Preferred monomers include TFE and HFP, but may also contain smaller amounts of monomers from Formula I, such as PPVE. In many instances, the levels of VF2 in the major component may be as low as 15 wt% or 10 wt%, and in some aspects as low as 5 wt%. Commercially available polymers useful in this aspect of the invention include THV 200, THV500, and THV815 from Dyneon.

30 The minor component for this blend is chosen from either the group of perfluorinated fluoropolymers or those formed from copolymers of fluorine free monomers with fluorine containing monomers. A group of preferred materials for the minor component in this blend are those that contain substantially different levels of hydrogen containing monomers than does the

major component. Examples of this group include copolymers of TFE with HFP and/or a PAVE such as PPVE.

A preferred group of fluoropolymers, that is particularly well suited for use as the minor component in the formation of a blend of the invention (with any major component), are those copolymers which contain higher levels of perfluoroalkylvinylether or perfluoroalkoxyvinylether monomers and at least one copolymerizable comonomer. This group may be considered as a subset of any of the before mentioned classes of fluoropolymers, but it is not limited to being semi-crystalline. Typically the level of these specific monomers will be such that the fluoropolymer is nearly or completely amorphous and lack a discernable or appreciable melting point as determined by DSC (differential scanning calorimetry). The relatively high amounts of these monomers in the minor component fluoropolymer contributes to the immiscibility required of the blend.

Preferred comonomers for forming this class of minor component that are rich in PAVes and/or PAOVes include primarily TFE and VF2. Preferably, the fluoropolymer will contain at least 3 mole percent (mol%), more preferably at least about 5 mol%, of VF2 or other hydrogen containing monomers. When there is less than 3 mol% of VF2, the fluoropolymer will contain a perfluoro alkoxy vinyl ether monomer.

The uniqueness of this group of fluoropolymers allows them to be used as the minor component to form a fluoropolymer blend with any of the before mentioned semi-crystalline, melt processable fluoropolymers, provided that the two components remain immiscible. Specific examples include FEP as the major component and copolymers of TFE and MV-31 as the minor and THV as the major and copolymers of VF2 and PMVE as the minor blend component. In addition, other minor component fluoropolymers as defined herein may be used in conjunction with these PAVE/ PAOVE materials.

Additives such as pigments, fillers, conductive agents and inorganic materials are often added to modify the properties of fluoropolymers. The ability to incorporate these materials and to achieve good dispersion and distribution of them throughout the fluoropolymer matrix can be difficult. Interactions between the fluoropolymer and the additive can lead to reactions that may degrade either component. These interactions can also cause substantial decreases in the MFI (increasing melt viscosity) of the resulting compound, which further hinders its processability. In addition, this rise in viscosity can lead to overheating of the compound during processing that can lead to further degradation of the fluoropolymer.

It has now been found that the addition of a minor blend component along with the additive to the major blend component can substantially mitigate the interactions between the additive and the major blend component. The fluoropolymer blends of the invention may also serve to improve the dispersion of additives that are otherwise difficult to incorporate into the major blend component. In general, the fluoropolymers that are chosen as the minor blend component to improve the dispersion of the additive are from the same previously described classes of fluoropolymers and the same teachings for selection of the major and minor component apply.

One or more additive(s) may be incorporated into the fluoropolymer blend via any known means. For example, the additive may be pre-blended into the minor component and this mixture subsequently can be added to the major component. Alternatively, the additive(s) and minor component(s) together can be added to the major component(s) using one blending procedure. When the additive is pre-blended into the minor component, the amount of minor component in the final fluoropolymer blend may be as high as 20% by weight or higher.

In one embodiment the viscosity of the minor component may be significantly lower than that of the major component to aid the incorporation of the additive. This difference in viscosity between the two fluoropolymer components may be an order of magnitude or greater, or even two orders of magnitude or greater.

In another embodiment, the minor component is chosen such that it has less of an interaction or interference with the additive than the major component. This embodiment of the invention helps incorporate an additive into the major blend component. An easy test to determine if a fluoropolymer is less interfering than another is to make a simple melt compound of the additive and the fluoropolymer and compare it to the compound of another fluoropolymer with the additive. The interactions that may occur include discoloration, off gassing, and changes in viscosity. Examples of reactive fluoropolymers are those which comprise partially fluorinated monomers.

While the minor component may aid in the process of dispersing the additive, the other benefits it provides to the fluoropolymer blend may be diminished by the presence of the additive in some embodiments. Means to minimize or even overcome this effect may be as simple as increasing the amount of the minor component fluoropolymer in the blend. An alternative is to provide an additional minor component to the blend. In this embodiment, one of the minor component fluoropolymers may serve primarily to improve the dispersion of the additive, while the other aids in the processing of the major component. The minor component

that is intended for improving the processing of the overall blend can be added as the final ingredient after pre-blending the other components to minimize any adverse interactions with the rest of the mixture.

The blends of the invention can provide a variety of improvements to the extrusion process. In comparison to the extrusion of major component by itself, the inventive fluoropolymer blend can reduce the torque, and/or pressure in an extrusion process. It may also reduce surface defects such as melt fracture and improve the surface finish of extruded articles. Further, the addition of the minor component, even at very low levels, can minimize the formation of die drool that could otherwise occur from the major component. The inventive fluoropolymer blends may also allow for the processing of the major component at conditions that are otherwise not feasible for the major component, such as at colder temperatures and/or higher shear rates, and can allow for the economical processing of higher molecular weight major components to gain their benefits. The invention may also provide for improved control of the extrudate dimensions, such as caliper of wire coatings. Any of these listed benefits may occur either singly or in combination with others.

Depending on the selection and usage levels of the materials used to form the fluoropolymer blend, the benefits described above may occur almost instantaneously or more slowly over a period of time. If desired, the time for these benefits to present themselves may be lessened by using a higher concentration of the minor component at the outset of the extrusion process. This initial procedure may then be followed by the intended concentration of the FP blend for formation of the end-use article. Alternatively, the major component may be extruded alone for a period of time to receive the benefits of the fluoropolymer blend while the effect of the minor component still lingers in the extrusion equipment.

The inventive fluoropolymer blends provide benefits to known extrusion processes. In general, a single screw extruder or other device is employed to pump the blend through a die or tool to shape the extrudate into the desired form, such as a film, sheet, rod, tube, hose, wire coating, laminates, containers, and the like. End use articles produced from extrusion processes include, *e.g.*, films, foils, hoses, wires, cables, coatings, laminates, bottles, and drums for applications such as chemical barriers, fluid transport, communications cables and chemical containment.

## Examples

### Materials

All monomers are reported as nominal values in weight percent. All polymers were commercially available or produced by known methods for aqueous emulsion polymerization.

#### 5 FP (fluoropolymer) Description

- A Dyneon HTE X 1705, a semi-crystalline copolymer of 12% ethylene, 61% TFE, 27% HFP
- B Dyneon FEP 6322, a semi-crystalline copolymer of 86% TFE, 14% HFP
- C Dyneon PFA 6613N, a semi-crystalline copolymer of 96% TFE, 4% PPVE-1
- 10 D Dyneon THV 220G, a semi-crystalline copolymer of 40% TFE, 40% VF2 and 20% HFP
- E Semi-crystalline copolymer of 76% TFE, 13% VF2 and 11% HFP
- F Amorphous copolymer of 30% VF2, 14% TFE, 56% MV-31 and less than 1% of BTFE (bromotrifluoroethylene)
- 15 G Amorphous copolymer of 78% TFE, 21% propylene, less than 1% BTFE
- H Dynamar FX-9613, an amorphous copolymer of 60% VF2 and 40% HFP
- I Semi-crystalline copolymer of 88% TFE, 12% propylene
- J Dyneon ET 6235, a semi-crystalline copolymer of ethylene, TFE and PPVE-1
- K Dynamar PPA-2231, an amorphous copolymer of 60% VF2 and 40% HFP
- 20 L Amorphous copolymer of 51% TFE, 48% MV-31, less than 1% BTFE
- M Dyneon HTE X 1500, semi-crystalline copolymer of 12% ethylene, 61% TFE, 27% HFP
- N Semi-crystalline copolymer of 38% TFE, 40% VF2, 18% HFP and 4% PPVE-1

#### 25 Example 1

A fluoropolymer blend was prepared by tumbling a pellet mixture of 2 lbs (908 g) of FP-A with 18 lbs (8.18 kg) of FP-B. The blend was then feed to a 2 inch (5.08cm) Davis Standard wire coating extruder with a mixing screw that was fitted with a GenCa 510 cross-head. The die and pin set used in the cross-head were 0.380 and 0.220 inches (9.65mm and 5.59mm) respectively. The temperatures of the extruder were set to deliver a melt temperature of 700°F (371°C) and the screw rpm's were set to give an output that would coat 7 mils (178µm) of insulation onto 20 mil (508µm) copper wire at 1500 fpm (457mpm). Within minutes after the addition of the blend, the tubular extrudate was opaque and smooth and the pressure in the extruder had decreased about 35%. In addition, there were no visible signs of die drool or phase separation from the blend. This blend was immediately followed by the extrusion of pure FP-B. When the extrudate returned to transparent, indicating that the blend had largely exited the die, it remained free of melt fracture for a period of about 10 minutes.

The melt fracture gradually reappeared over a period of about 5 more minutes and the pressure eventually returned to the previous starting value.

#### **Comparative Example 1 (CE-1)**

5 The extruder used in Example 1 was cleaned to bare metal and a sample of pure FP-B was feed at the same extrusion conditions. The extrudate exhibited severe melt fracture. At these conditions, nominal 20 mil (508 $\mu$ m) copper wire was coated to an average diameter of 34 mils (864  $\mu$ m). The resulting wire had a rough finish and subsequent analysis indicated the diameter down a 6 ft. (1.83m) length of the wire varied by about +/- 4 mils (+/- 102  $\mu$ m). The copper wire that was being coated had by itself a variation of less than +/- 0.1 mils (+/- 2.5  $\mu$ m) indicating that most of the variation in the coated wire sample was occurring within the fluoropolymer coating.

#### **Example 2**

Following the procedure of Example 1, another blend was prepared containing 5% of FP-A and 95% FP-B. The two resins were feed to the extruder and a similar effect was observed as in example 1. After the blend had exited the die, the extruder was feed with only FP-B and copper was threaded through the die and the wire coating process begun. Both the inner and outer surfaces of the extrudate were visibly free of melt fracture. The resulting wire had a nominal diameter of 34 mils (864  $\mu$ m) with a variation of about +/- 0.5 mils (12.7  $\mu$ m).

#### **Comparative Example 2 (CE-2)**

20 Wire was prepared according to CE-1, but the extruder was adjusted to deliver a melt temperature of 760°F (404°C). The outside of the extrudate was smooth and the inside had a faint frosted appearance indicating mild melt fracture. The resulting wire had a diameter variation of about +/- 1.5 mil (38  $\mu$ m).

#### **Example 3**

25 A FP blend of 5% of FP-A and 95% FP-B was melt-compounded on a Berstorff twin screw extruder and extruded into pellets. The pellets had a white, opaque appearance and optical microscopy revealed the minor component to be well dispersed and distributed within the major component fluoropolymer. A portion of this blend was feed at a ratio of 1 part by weight of the blend with 4 parts of FP-B to the wire coating extruder used in Example 1. The extruder was operated under similar conditions to that of Example 1 and within 30 minutes the extrudate of FP-B, which contained 1% of the minor component FP-A, was visibly free of melt fracture. In contrast to comparative Example 2, the resulting wire of this experiment had a smoother

finish and less diameter variation. The tensile and elongation properties of the wire were determined according to UL test method 444. Samples were tested both before and after heat aging (7days @ 232 C) and did not show any significant deviation from the sample produced in comparative example 2. This indicates that the presence of the minor component did not negatively affect the mechanical properties of the major component FP used to coat the wire.

#### Examples 4 through 11 and Comparative Examples 3 through 6

The following sets of experiments were conducted to show the changes in extrusion performance and/or changes in surface appearance of various fluoropolymer blends. The individual fluoropolymers utilized were in either pellet or powder form or in the form of small cubes about the size of the pellets. Fluoropolymer blends were produced by tumbling 5 wt% of a minor component along with 95 wt% of a major component and feeding the mixture to a Brabender single screw extruder equipped with a rod die. The die had a 0.1125 inch (2.9 mm) diameter orifice and was fitted with a die tip heater. Before extruding any of the blends, the major component of a given blend was first extruded by itself. The output rate and temperature settings of the extruder and die were adjusted until the major component exhibited severe sharkskin-type melt fracture. The FP blend was then extruded under the same conditions and observed for changes in extrusion pressure and torque, or for changes in the appearance of the extrudate, in comparison to the major component. In between each experiment, the major component was extruded by itself to re-establish the starting conditions. In some instances, the extruder was disassembled and cleaned.

Examples 4 through 6; see results in Table 1

**Table 1**

Experiment	Major	Minor	Melt temp.	% Pressure Decrease	Appearance
Ex. 4	FP-B	FP-A	371	65	smooth, milky
Ex. 5	FP-B	FP-E	371	8	smooth, clear
Ex. 6	FP-B	FP-F	371	25	clear, smooth

#### Example 7

A blend of 5% FP-G and 95% FP-B was extruded under the same conditions of example 4 to demonstrate the method claim of the invention. The blend had a 15% drop in extrusion



pressure compared to FP-B. The extrudate appeared free of melt fracture, but had a rough surface believed to be caused by the poor quality of dispersion in the fluoropolymer blend.

### **Comparative Example 3 (CE-3)**

5 A blend of 5% of an amorphous copolymer of VF2 and HFP (FP-H) and 95% FP-B was extruded under the same conditions as Example 4. The extrudate was brown and full of bubbles.

### **Example 8**

A fluoropolymer blend of 5% of FP-J and 95% of FP-C was extruded under the same conditions as Example 4, except an extrusion temperature of 360°C was used. The extrudate had a smooth surface and was less translucent than FP-C.

### **10 Example 9**

The procedure of Example 8 was repeated except that FP-J was substituted for the minor component. About a 20% decrease in extrusion pressure occurred and the extrudate was smooth and opaque.

### **Comparative example 4**

15 The procedure of Example 8 was repeated except that FP-K was substituted for the minor component. The extrudate was tan and contained bubbles.

### **Example 10**

20 The procedure of Example 8 was repeated except that FP-L was substituted for the minor component and FP-D was substituted for the major component. The extrusion temperature was set at 210°C and the die tip heater was not used. The torque during extrusion was about 5% less than FP-D alone. The extrudate was melt fractured and milky in appearance.

### **Example 11**

25 The procedure of Example 10 was repeated except that FP-M was substituted for the minor component. The torque during extrusion was about 10% less than FP-D alone. The extrudate was melt fractured and clear in appearance.

### **Comparative Example 5**

30 The procedure of Example 10 was repeated except that FP-N was substituted for the minor component. There were no changes in torque or pressure during extrusion. The extrudate was transparent and the melt fracture appeared worse than that of FP-D when it was extruded alone.

### Comparative Example 6

The procedure of comparative Example 10 was repeated except that FP-H was substituted for the minor component. There were no changes in torque or pressure during extrusion. The extrudate was opaque and exhibited melt fracture.

5

Various modifications and alterations of this invention will become apparent to those skilled in the art without departing from the scope and principles of this invention, and it should be understood that this invention is not to be unduly limited to the illustrative embodiments set forth hereinabove. All publications and patents are herein incorporated by reference to the same

10 extent as if each individual publication or patent was specifically and individually incorporated by reference.

11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100  
101  
102  
103  
104  
105  
106  
107  
108  
109  
110  
111  
112  
113  
114  
115  
116  
117  
118  
119  
120  
121  
122  
123  
124  
125  
126  
127  
128  
129  
130  
131  
132  
133  
134  
135  
136  
137  
138  
139  
140  
141  
142  
143  
144  
145  
146  
147  
148  
149  
150  
151  
152  
153  
154  
155  
156  
157  
158  
159  
160  
161  
162  
163  
164  
165  
166  
167  
168  
169  
170  
171  
172  
173  
174  
175  
176  
177  
178  
179  
180  
181  
182  
183  
184  
185  
186  
187  
188  
189  
190  
191  
192  
193  
194  
195  
196  
197  
198  
199  
200  
201  
202  
203  
204  
205  
206  
207  
208  
209  
210  
211  
212  
213  
214  
215  
216  
217  
218  
219  
220  
221  
222  
223  
224  
225  
226  
227  
228  
229  
230  
231  
232  
233  
234  
235  
236  
237  
238  
239  
240  
241  
242  
243  
244  
245  
246  
247  
248  
249  
250  
251  
252  
253  
254  
255  
256  
257  
258  
259  
260  
261  
262  
263  
264  
265  
266  
267  
268  
269  
270  
271  
272  
273  
274  
275  
276  
277  
278  
279  
280  
281  
282  
283  
284  
285  
286  
287  
288  
289  
290  
291  
292  
293  
294  
295  
296  
297  
298  
299  
300  
301  
302  
303  
304  
305  
306  
307  
308  
309  
310  
311  
312  
313  
314  
315  
316  
317  
318  
319  
320  
321  
322  
323  
324  
325  
326  
327  
328  
329  
330  
331  
332  
333  
334  
335  
336  
337  
338  
339  
340  
341  
342  
343  
344  
345  
346  
347  
348  
349  
350  
351  
352  
353  
354  
355  
356  
357  
358  
359  
360  
361  
362  
363  
364  
365  
366  
367  
368  
369  
370  
371  
372  
373  
374  
375  
376  
377  
378  
379  
380  
381  
382  
383  
384  
385  
386  
387  
388  
389  
390  
391  
392  
393  
394  
395  
396  
397  
398  
399  
400  
401  
402  
403  
404  
405  
406  
407  
408  
409  
410  
411  
412  
413  
414  
415  
416  
417  
418  
419  
420  
421  
422  
423  
424  
425  
426  
427  
428  
429  
430  
431  
432  
433  
434  
435  
436  
437  
438  
439  
440  
441  
442  
443  
444  
445  
446  
447  
448  
449  
450  
451  
452  
453  
454  
455  
456  
457  
458  
459  
460  
461  
462  
463  
464  
465  
466  
467  
468  
469  
470  
471  
472  
473  
474  
475  
476  
477  
478  
479  
480  
481  
482  
483  
484  
485  
486  
487  
488  
489  
490  
491  
492  
493  
494  
495  
496  
497  
498  
499  
500  
501  
502  
503  
504  
505  
506  
507  
508  
509  
510  
511  
512  
513  
514  
515  
516  
517  
518  
519  
520  
521  
522  
523  
524  
525  
526  
527  
528  
529  
530  
531  
532  
533  
534  
535  
536  
537  
538  
539  
540  
541  
542  
543  
544  
545  
546  
547  
548  
549  
550  
551  
552  
553  
554  
555  
556  
557  
558  
559  
560  
561  
562  
563  
564  
565  
566  
567  
568  
569  
570  
571  
572  
573  
574  
575  
576  
577  
578  
579  
580  
581  
582  
583  
584  
585  
586  
587  
588  
589  
590  
591  
592  
593  
594  
595  
596  
597  
598  
599  
600  
601  
602  
603  
604  
605  
606  
607  
608  
609  
610  
611  
612  
613  
614  
615  
616  
617  
618  
619  
620  
621  
622  
623  
624  
625  
626  
627  
628  
629  
630  
631  
632  
633  
634  
635  
636  
637  
638  
639  
640  
641  
642  
643  
644  
645  
646  
647  
648  
649  
650  
651  
652  
653  
654  
655  
656  
657  
658  
659  
660  
661  
662  
663  
664  
665  
666  
667  
668  
669  
670  
671  
672  
673  
674  
675  
676  
677  
678  
679  
680  
681  
682  
683  
684  
685  
686  
687  
688  
689  
690  
691  
692  
693  
694  
695  
696  
697  
698  
699  
700  
701  
702  
703  
704  
705  
706  
707  
708  
709  
710  
711  
712  
713  
714  
715  
716  
717  
718  
719  
720  
721  
722  
723  
724  
725  
726  
727  
728  
729  
730  
731  
732  
733  
734  
735  
736  
737  
738  
739  
740  
741  
742  
743  
744  
745  
746  
747  
748  
749  
750  
751  
752  
753  
754  
755  
756  
757  
758  
759  
760  
761  
762  
763  
764  
765  
766  
767  
768  
769  
770  
771  
772  
773  
774  
775  
776  
777  
778  
779  
780  
781  
782  
783  
784  
785  
786  
787  
788  
789  
790  
791  
792  
793  
794  
795  
796  
797  
798  
799  
800  
801  
802  
803  
804  
805  
806  
807  
808  
809  
810  
811  
812  
813  
814  
815  
816  
817  
818  
819  
820  
821  
822  
823  
824  
825  
826  
827  
828  
829  
830  
831  
832  
833  
834  
835  
836  
837  
838  
839  
840  
841  
842  
843  
844  
845  
846  
847  
848  
849  
850  
851  
852  
853  
854  
855  
856  
857  
858  
859  
860  
861  
862  
863  
864  
865  
866  
867  
868  
869  
870  
871  
872  
873  
874  
875  
876  
877  
878  
879  
880  
881  
882  
883  
884  
885  
886  
887  
888  
889  
890  
891  
892  
893  
894  
895  
896  
897  
898  
899  
900  
901  
902  
903  
904  
905  
906  
907  
908  
909  
910  
911  
912  
913  
914  
915  
916  
917  
918  
919  
920  
921  
922  
923  
924  
925  
926  
927  
928  
929  
930  
931  
932  
933  
934  
935  
936  
937  
938  
939  
940  
941  
942  
943  
944  
945  
946  
947  
948  
949  
950  
951  
952  
953  
954  
955  
956  
957  
958  
959  
960  
961  
962  
963  
964  
965  
966  
967  
968  
969  
970  
971  
972  
973  
974  
975  
976  
977  
978  
979  
980  
981  
982  
983  
984  
985  
986  
987  
988  
989  
990  
991  
992  
993  
994  
995  
996  
997  
998  
999  
1000  
1001  
1002  
1003  
1004  
1005  
1006  
1007  
1008  
1009  
1010  
1011  
1012  
1013  
1014  
1015  
1016  
1017  
1018  
1019  
1020  
1021  
1022  
1023  
1024  
1025  
1026  
1027  
1028  
1029  
1030  
1031  
1032  
1033  
1034  
1035  
1036  
1037  
1038  
1039  
1040  
1041  
1042  
1043  
1044  
1045  
1046  
1047  
1048  
1049  
1050  
1051  
1052  
1053  
1054  
1055  
1056  
1057  
1058  
1059  
1060  
1061  
1062  
1063  
1064  
1065  
1066  
1067  
1068  
1069  
1070  
1071  
1072  
1073  
1074  
1075  
1076  
1077  
1078  
1079  
1080  
1081  
1082  
1083  
1084  
1085  
1086  
1087  
1088  
1089  
1090  
1091  
1092  
1093  
1094  
1095  
1096  
1097  
1098  
1099  
1100  
1101  
1102  
1103  
1104  
1105  
1106  
1107  
1108  
1109  
1110  
1111  
1112  
1113  
1114  
1115  
1116  
1117  
1118  
1119  
1120  
1121  
1122  
1123  
1124  
1125  
1126  
1127  
1128  
1129  
1130  
1131  
1132  
1133  
1134  
1135  
1136  
1137  
1138  
1139  
1140  
1141  
1142  
1143  
1144  
1145  
1146  
1147  
1148  
1149  
1150  
1151  
1152  
1153  
1154  
1155  
1156  
1157  
1158  
1159  
1160  
1161  
1162  
1163  
1164  
1165  
1166  
1167  
1168  
1169  
1170  
1171  
1172  
1173  
1174  
1175  
1176  
1177  
1178  
1179  
1180  
1181  
1182  
1183  
1184  
1185  
1186  
1187  
1188  
1189  
1190  
1191  
1192  
1193  
1194  
1195  
1196  
1197  
1198  
1199  
1200  
1201  
1202  
1203  
1204  
1205  
1206  
1207  
1208  
1209  
1210  
1211  
1212  
1213  
1214  
1215  
1216  
1217  
1218  
1219  
1220  
1221  
1222  
1223  
1224  
1225  
1226  
1227  
1228  
1229  
1230  
1231  
1232  
1233  
1234  
1235  
1236  
1237  
1238  
1239  
1240  
1241  
1242  
1243  
1244  
1245  
1246  
1247  
1248  
1249  
1250  
1251  
1252  
1253  
1254  
1255  
1256  
1257  
1258  
1259  
1260  
1261  
1262  
1263  
1264  
1265  
1266  
1267  
1268  
1269  
1270  
1271  
1272  
1273  
1274  
1275  
1276  
1277  
1278  
1279  
1280  
1281  
1282  
1283  
1284  
1285  
1286  
1287  
1288  
1289  
1290  
1291  
1292  
1293  
1294  
1295  
1296  
1297  
1298  
1299  
1300  
1301  
1302  
1303  
1304  
1305  
1306  
1307  
1308  
1309  
1310  
1311  
1312  
1313  
1314  
1315  
1316  
1317  
1318  
1319  
1320  
1321  
1322  
1323  
1324  
1325  
1326  
1327  
1328  
1329  
1330  
1331  
1332  
1333  
1334  
1335  
1336  
1337  
1338  
1339  
1340  
1341  
1342  
1343  
1344  
1345  
1346  
1347  
1348  
1349  
1350  
1351  
1352  
1353  
1354  
1355  
1356  
1357  
1358  
1359  
1360  
1361  
1362  
1363  
1364  
1365  
1366  
1367  
1368  
1369  
1370  
1371  
1372  
1373  
1374  
1375  
1376  
1377  
1378  
1379  
1380  
1381  
1382  
1383  
1384  
1385  
1386  
1387  
1388  
1389  
1390  
1391  
1392  
1393  
1394  
1395  
1396  
1397  
1398  
1399  
1400  
1401  
1402  
1403  
1404  
1405  
1406  
1407  
1408  
1409  
1410  
1411  
1412  
1413  
1414  
1415  
1416  
1417  
1418  
1419  
1420  
1421  
1422  
1423  
1424  
1425  
1426  
1427  
1428  
1429  
1430  
1431  
1432  
1433  
1434  
1435  
1436  
1437  
1438  
1439  
1440  
1441  
1442  
1443  
1444  
1445  
1446  
1447  
1448  
1449  
1450  
1451  
1452  
1453  
1454  
1455  
1456  
1457  
1458  
1459  
1460  
1461  
1462  
1463  
1464  
1465  
1466  
1467  
1468  
1469  
1470  
1471  
1472  
1473  
1474  
1475  
1476  
1477  
1478  
1479  
1480  
1481  
1482  
1483  
1484  
1485  
1486  
1487  
1488  
1489  
1490  
1491  
1492  
1493  
1494  
1495  
1496  
1497  
1498  
1499  
1500  
1501  
1502  
1503  
1504  
1505  
1506  
1507  
1508  
1509  
1510  
1511  
1512  
1513  
1514  
1515  
1516  
1517  
1518  
1519  
1520  
1521  
1522  
1523  
1524  
1525  
1526  
1527  
1528  
1529  
1530  
1531  
1532  
1533  
1534  
1535  
1536  
1537  
1538  
1539  
1540  
1541  
1542  
1543  
1544  
1545  
1546  
1547  
1548  
1549  
1550  
1551  
1552  
1553  
1554  
1555  
1556  
1557  
1558  
1559  
1560  
1561  
1562  
1563  
1564  
1565  
1566  
1567  
1568  
1569  
1570  
1571  
1572  
1573  
1574  
1575  
1576  
1577  
1578  
1579  
1580  
1581  
1582  
1583  
1584  
1585  
1586  
1587  
1588  
1589  
1590  
1591  
1592  
1593  
1594  
1595  
1596  
1597  
1598  
1599  
1600  
1601  
1602  
1603  
1604  
1605  
1606  
1607  
1608  
1609  
1610  
1611  
1612  
1613  
1614  
1615  
1616  
1617  
1618  
1619  
1620  
1621  
1622  
1623  
1624  
1625  
1626  
1627  
1628  
1629  
1630  
1631  
1632  
1633  
1634  
1635  
1636  
1637  
1638  
1639  
1640  
1641  
1642  
1643  
1644  
1645  
1646  
1647  
1648  
1649  
1650  
1651  
1652  
1653  
1654  
1655  
1656  
1657  
1658  
1659  
1660  
1661  
1662  
1663  
1664  
1665  
1666  
1667  
1668  
1669  
1670  
1671  
1672  
1673  
1674  
1675  
1676  
1677  
1678  
1679  
1680  
1681  
1682  
1683  
1684  
1685  
1686  
1687  
1688  
1689  
1690  
1691  
1692  
1693  
1694  
1695  
1696  
1697  
1698  
1699  
1700  
1701  
1702  
1703  
1704  
1705  
1706  
1707  
1708  
1709  
1710  
1711  
1712  
1713  
1714  
1715  
1716  
1717  
1718  
1719  
1720  
1721  
1722  
1723  
1724  
1725  
1726  
1727  
1728  
1729  
1730  
1731  
1732  
1733  
1734  
1735  
1736  
1737  
1738  
1739  
1740  
1741  
1742  
1743  
1744  
1745  
1746  
1747  
1748  
1749  
1750  
1751  
1752  
1753  
1754  
1755  
1756  
1757  
1758  
1759  
1760  
1761  
1762  
1763  
1764  
1765  
1766  
1767  
1768  
1769  
1770  
1771  
1772  
1773  
1774  
1775  
1776  
1777  
1778  
1779  
1780  
1781  
1782  
1783  
1784  
1785  
1786  
1787  
1788  
1789  
1790  
1791  
1792  
1793  
1794  
1795  
1796  
1797  
1798  
1799  
1800  
1801  
1802  
1803  
1804  
1805  
1806  
1807  
1808  
1809  
1810  
1811  
1812  
1813  
1814  
1815  
1816  
1817  
1818  
1819  
1820  
1821  
1822  
1823  
1824  
1825  
1826  
1827  
1828  
1829  
1830  
1831  
1832  
1833  
1834  
1835  
1836  
1837  
1838  
1839  
1840  
1841  
1842  
1843  
1844  
1845  
1846  
1847  
1848  
1849  
1850  
1851  
1852  
1853  
1854  
1855  
1856  
1857  
1858  
1859  
1860  
1861  
1862  
1863  
1864  
1865  
1866  
1867  
1868  
1869  
1870  
1871  
1872  
1873  
1874  
1875  
1876  
1877  
1878  
1879  
1880  
1881  
1882  
1883  
1884  
1885  
1886  
1887  
1888  
1889  
1890  
1891  
1892  
1893  
1894  
1895  
1896  
1897  
1898  
1899  
1900  
1901  
1902  
1903  
1904  
1905  
1906  
1907  
1908  
1909  
1910  
1911  
1912  
1913  
1914  
1915  
1916  
1917  
1918  
1919  
1920  
1921  
1922  
1923  
1924  
1925  
1926  
1927  
1928  
1929  
1930  
1931  
1932  
1933  
1934  
1935  
1936  
1937  
1938  
1939  
1940  
1941  
1942  
1943  
1944  
1945  
1946  
1947  
1948  
1949  
1950  
1951  
1952  
1953  
1954  
1955  
1956  
1957  
1958  
1959  
1960  
1961  
1962  
1963  
1964  
1965  
1966  
1967  
1968  
1969  
1970  
1971  
1972  
1973  
1974  
1975  
1976  
1977  
1978  
1979  
1980  
1981  
1982  
1983  
1984  
1985  
1986  
1987  
1988  
1989  
1990  
1991  
1992  
1993  
1994  
1995  
1996  
1997  
1998  
1999  
2000  
2001  
2002  
2003  
2004  
2005  
2006  
2007  
2008  
2009  
2010  
2011  
2012  
2013  
2014  
2015  
2016  
2017  
2018  
2019  
2020  
2021  
2022  
2023  
2024  
2025  
2026  
2027  
2028  
2029  
2030  
2031  
2032  
2033  
2034  
2035  
2036  
2037  
2038  
2039  
2040  
2041  
2042  
2043  
2044  
2045  
2046  
2047  
2048  
2049  
2050  
2051  
2052  
2053  
2054  
2055  
2056  
2057  
2058  
2059  
2060  
2061  
2062  
2063  
2064  
2065  
2066  
2067  
2068  
2069  
2070  
2071  
2072  
2073  
2074  
2075  
2076  
2077  
2078  
2079  
2080  
2081  
2082  
2083  
2084  
2085  
2086  
2087  
2088  
2089  
2090  
2091  
2092  
2093  
2094  
2095  
2096  
2097  
2098  
2099  
2100  
2101  
2102  
2103  
2104  
2105  
2106  
2107  
2108  
2109  
2110  
2111  
2112  
2113  
2114  
2115  
2116  
2117  
2118  
2119  
2120  
2121  
2122  
2123  
2124  
2125  
2126  
2127  
2128  
2129  
2130  
2131  
2132  
2133  
2134  
2135  
2136  
2137  
2138  
2139  
2140  
2141  
2142  
2143  
2144  
2145  
2146  
2147  
2148  
2149  
2150  
2151  
2152  
2153  
2154  
2155  
2156  
2157  
2158  
2159  
2160  
2161  
2162  
2163  
2164  
2165  
2166  
2167  
2168  
2169  
2170  
2171  
2172  
2173  
2174  
2175  
2176  
2177  
2178  
2179  
2180  
2181  
2182  
2183  
2184  
2185  
2186  
2187  
2188  
2189  
2190  
2191  
2192  
2193  
2194  
2195  
2196  
2197  
2198  
2199  
2200  
2201  
2202  
2203  
2204  
22